



CORRILO-CB 30W CDL-CB-30



 Luminaire shape

 Body color



Die cast Aluminium Body



IP44 Rated



IP20 Rated Control gear



50000 Hrs Lifetime


CorriLO-CB is a versatile recessed down light that can be used widely in indoors, easy to mount on the ceiling recess. The luminaire offering a broad range of power, color temperatures and options like motion detection, timer, sleep and twilight function.

This range of products are popular for a wide range of application such as office spaces, Conference Halls, shops, residential and other indoor spaces.

Luminaire Details:



Product Name	: CorriLO-CB
Product Type	: LED Recessed Down Light
Product code	: CDL-CB-30
Efficiency Classification	: Class B
Luminaire Type	: SMD
Fixture Type	: Fixed

Correlated Color Temperature:



Light Source Details:

Light Emission	: Spot Emission
Source brand	: CREE
Rated Power	: 30W
CRI	: >80
UGR	: <19
McAdam Binning	: Step 3

CCT	Rated Lumens
 3000K	2790lms
 4000K	2850lms
 5000K	3000lms
 6500K	3150lms

Luminaire Housing:

Body	: Die cast Aluminium
Reflector type	: Aluminium
Lens/Diffuser	: Center frosted glass
Storage Temperature (Ts)	: -40 to 60°C
Ambient Temperature (Ta)	: -20 to 50°C
Humidity	: RH 10-90 %

5 Years Product Warranty

Control Gear Specifications:

Control Gear Brand	: Hansa Green
Input Voltage	: 220-240V AC
Input Current	: 0.13A
Frequency	: 50/60Hz
Output Voltage	: 25-45 V DC Max.
Output Current	: 750 mA
Max. Output power	: 30W
Power Factor	: >0.9
THD	: <15%
Case temperature(Tc)	: 80°C
Ambient Temperature	: -20 to 60 C
Over voltage protection	: Available
Short circuit Protection	: Available
No-Load Protection	: Available
Burst Protection Voltage	: 1KV
Surge Protection Voltage	: 1KV(L to N) & 2KV(L/N to Earth)

Control Gear Compatibility:

Control Gear is the driving unit of LED. Corriilo-CB is compatible with Phase cut dimming, 0-10/1-10V dimming and DALI Dimming control gears.



Optics and Beam Angle:

95° Optics




Add-on sensor Compatibility:



Corriilo-CB is compatible with external add-on motion detection and daylight sensors.

Photometric Details:

Photometric testing provides a comprehensive laboratory service for testing the amount, colour, quality and spatial distribution of light emitted from lamps, LEDs and luminaires. The standard photometric data files in IES (.ies) and EULUMDAT (.ldt) formats per IES LM 79-08 and BS EN 13032




Emergency Compatibility:

Corriilo-CB is compatible with emergency kits

Ordering Codes

CCT	Code
3000K	629050030521
4000K	629050030541
5000K	629050030561
6500K	629050030591

Physical Dimensions:



Diameter(W)	: 225 mm
Height(H)	: 63 mm
Cut out	: 200 mm